

Tender Inviting Authority: S.O(Civil), Rajrappa Area

Name of Work :- Providing APP over roof of administrative office of Rajrappa Project under Rajrappa Project.

	Category of Services (To Be Selected by Department)	Category of Bidder( To Be Selected by Bidder)	To Be Entered by Department		
ITC Available	Works Contract	Bidder's Status (Mandatory)	Rate of GST (in %)	GST to be Paid By Bidder (in Rs.)	GST to be Paid By CIL/Subsidiary (in Rs.)
Name of the Bidder/ Bidding Firm / Company :		Select	18.00	0.00	0.00

**PRICE SCHEDULE**

(This BOQ template must not be modified/replaced by the bidder and the same should be uploaded after filling the relevent columns, else the bidder is liable to be rejected for this tender. Bidders are allowed to enter the Bidder Name and Values only )

NUMBER #	TEXT #	NUMBER #	TEXT #	NUMBER	NUMBER #	TEXT #
Sl. No.	Item Description	Quantity	Units	Estimated Rate in Rs. P	TOTAL AMOUNT in Rs. P	TOTAL AMOUNT In Words
1	2	3	4	5	6	7
1	Removal of App and disposal of debris within a distance of 150m as per instruction of engineer in-charge	1102.46	Sqm	39.27	43295.88	INR Forty Three Thousand Two Hundred & Ninety Five and Paise Eighty Eight Only
2	Grading roof for water proofing treatment withCement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm nominal size)	30.70	cum	7562.70	232174.89	INR Two Lakh Thirty Two Thousand One Hundred & Seventy Four and Paise Eighty Nine Only
3	Providing and laying APP (Atactic Polypropylene Polymer) modified prefabricated five layer 3 mm thick water proofing membrane, black finished reinforced with non-woven polyester matt consisting of a coat of bitumen primer for bitumen membrane @ 0.40 litre/sqm by the same membrane manufacture of density at 25°C, 0.87-0.89 kg/ litre and viscosity 70-160 cps. Over the primer coat the layer of membrane shall be laid using Butane Torch and sealing all joints etc, and preparing the surface complete. The vital physical and chemical parameters of the membrane shall be as under : Joint strength in longitudinal and transverse direction at 23°C as 650/ 450N/ 5cm. Tear strength in longitudinal and transverse direction as 300/ 250N. Softening point of membrane not less than 150°C. Cold flexibility shall be upto -2°C when tested in accordance with ASTM, D - F447. The test shall be conducted at the authorized lab of the	1212.700	Sqm	450.30	546078.81	INR Five Lakh Forty Six Thousand & Seventy Eight and Paise Eighty One Only
4	Total impact of GST for the purpose of CTC	1.000	Nos	0.00	0.00	INR Zero Only
Total in Figures					821549.58	INR Eight Lakh Twenty One Thousand Five Hundred & Forty Nine and Paise Fifty Eight Only
Quoted Rate in Figures			Select		0.00	INR Zero Only
Quoted Rate in Words	<b>INR Zero Only</b>					